

# 72LGX, 73LGX, and 75LGX Super Guard®



## 3/8" 70-Series LGX Chisel Chains Deliver Performance

### SPECIFICATIONS

Chain Pitch	3/8" 
Cutter Style	Chisel 
Kickback Reduction	Ramped Depth Gauge 
Sequence	LGX 
	JGX 
Recommended Bar Length	12-42" (30-107 cm) 
Recommended Saw Sizes	Gasoline-powered 3-6 cu. in. (50-100 cc) and smaller saws 
Recommended User	Commercial  Professional 

Long-lasting 70-series saw chain is designed for high performance, easy maintenance and loop consistency.

FEATURES	BENEFITS
<b>Advanced grind geometry</b>	<ul style="list-style-type: none"> <li>Improved out-of-box grind</li> <li>High performance in all cutting modes</li> <li>Extreme cutting efficiency, less feed force required</li> </ul>
<b>Blued cutters</b>	<ul style="list-style-type: none"> <li>Superior corrosion resistance</li> <li>Base-cutter hardness consistency</li> </ul>
<b>Tumbled parts</b>	<ul style="list-style-type: none"> <li>Smooth finish</li> <li>Improved joint articulation, combats tight joints</li> </ul>
<b>Clean ground gullets</b>	<ul style="list-style-type: none"> <li>Increases chip flow, less chain clogging</li> <li>No out-of-the box filing needed</li> </ul>
<b>Skip Sequence</b>	<ul style="list-style-type: none"> <li>Professionals using longer bar lengths may prefer the full-skip 72JGX, 73JGX, and 75JGX options</li> </ul>
	<ul style="list-style-type: none"> <li>Helps keep oil where it's needed, on the chain</li> <li>Directs oil to the critical rivet flange/hole interface</li> </ul>
	<ul style="list-style-type: none"> <li>Help carry oil around the full length of the guide bar's groove (<i>standard sequence chains only</i>)</li> </ul>
	<ul style="list-style-type: none"> <li>Top-plate witness mark makes accurate sharpening easier</li> </ul>
	<ul style="list-style-type: none"> <li>Oregon® patented OCS-01 steel</li> </ul>
	<ul style="list-style-type: none"> <li>Reduces vibration 25% or more at the handles</li> </ul>

# 72LGX, 73LGX, and 75LGX Super Guard®



## SHARPENING NOTES

- \* When using an OREGON® file guide, ALWAYS hold it level, 0°, flat on the Top Plate



## WARNING

Failure to follow filing instructions can increase the level of kickback which can result in severe injury to the saw operator or bystanders.

- Do not exceed the depth-gauge setting shown right.
- Always file depth gauges back to their original rounded or ramped shape after lowering.

## ANSI KICKBACK CLASSIFICATION

72, 73, and 75LGX/JGX are yellow-label chains. Though these chains have ramped depth gauges which reduce kickback energies, these are NOT low-kickback chains. These chains should be used ONLY by individuals with experience and specialized training for dealing with kickback.

## SHARPENING & GRINDING TOOL PART NUMBERS

	511AX 510A	31686	70502 (12)	OR 534-316A 5-3/4" Dia.	12211 (12)	22290 (10)

## SHARPENING & GRINDING ANGLES

	 7/32"	 25°	 10° *	 60°	 .025" / 0.6mm
	 3/16"	 25°	 10°	 55°	 .025" / 0.6mm

## SAW CHAIN REPLACEMENT PARTS AND NUMBERS (25 PACKS)



<b>72LGX/JGX</b>	P26197	P26198	P23837	P23910	P65715
<b>73LGX/JGX</b>	P26197	P26198	P23837	P23910	P68183
<b>75LGX/JGX</b>	P26197	P26198	P23837	P23921	P30927

Replacement parts come in packs of 25

## CHAIN GAUGE

	72LGX / JGX	73LGX / JGX	75LGX / JGX
	.050"	.058"	.063"

OREGON, Super Guard, Vibe-Ban and LubriWell are registered trademarks and LubriLink and Witness Mark are trademarks of Blount, Inc. For more information on these and other OREGON® products, contact your authorized OREGON® distributor, or:

**OREGON®, BLOUNT, INC.** PO Box 22127 · Portland, OR, U.S.A. 97269-2127 Phone: 503-653-8881 Fax: 503-653-4201 Web: oregonproducts.com  
**OREGON DISTRIBUTION LTD.** 505 Edinburgh Rd. N., Guelph, Ontario, Canada N1H 6L4 Phone: 519-822-6870 Fax: 519-822-4999